



LONGSHINE Technologie (Europe) GmbH

Post Address: P.O.Box 2246
House Address: An der Strusbek 9
WEB: <http://www.longshine.de>

D-22 912 Ahrensburg
D-22 926 Ahrensburg

Tel: ++49-(0)-4102-4922-0
Fax: ++49-(0)-4102-40109
E-MAIL: sales@longshine.de

LCS-FS9324

**24-Ports 10/100 Mbit/s
Webmanaged Workgroupswitch
without fan**



The **LCS-FS9324** Switch has 24 Ports 10/100Mbps, all 24 Ports support Auto-negotiation and Auto MDI/MDI-X. The Switch is suitable for all situations, like small workgroups, dividing network structures in segments or multimedia applications. The Switch features VLAN-function, trunking and QoS. You can configure all functions comfortable over the implemented web interface and/or over the console port.

Features:

- ◆ Interface: 24 * RJ-45 for 10BASE-T and 100BASE-TX
- ◆ Supports local console port and web based Userinterface
- ◆ Supports Auto MDI-/MDI-X
- ◆ Supports bandwidth control on every port
- ◆ Supports back-pressure flow control for half-duplex
- ◆ Head of line blocking prevention
- ◆ Supports 3 different Types of QoS, TOS/DiffServ (DS)
- ◆ Supports up to 4 ports and 6 groups for port aggregation
- ◆ Supports 24 entries for VLANs
- ◆ 19" Case
- ◆ Fanless
- ◆ Rich LEDs for diagnostics

Specifications:

Standards:	IEEE802.3 IEEE802.3u IEEE802.3x IEEE802.1p
Buffer Memory:	320 KBytes
MAC- Adresses :	8K
Backplane:	4,8 GB/s
Interface:	24 * 10/100Mbit/s 1 * RS-232 console port
Emission:	FCC Class A, CE Mark Class A, VCCI-A
Temperature:	0°C ~ 40°C, (32°F – 104°F)
Humidity:	10% ~ 90% (non-condensierend)
Dimensions:	441mm x 130mm x 44,1mm, 19"
Power Supply:	Internal switching power supply (100 ~ 240 VAC, 50~60Hz)
Box contains:	Switch, Manual, Manual on CD, Power cord, rubber feets, bracket for rackmount installation
EAN:	4016621004095