



KL-708M

Rack-Mount KVM

17" Console with

8 Port KVM



The Console KL-708M is totally modular. In its standard version comes with a monitor 17", in multiple language keyboard and a KVM from 8 ports. The design is very robust industrial and permitting to be drawn from telescopic form of the cabinet. The modules can be used without disassembly tools. The KVM management is performed by OSD menu on the screen. It incorporates two wires octopus type VGA, USB and 2x PS / 2 to 1.8 meters. The connection to your PC monitor, can be done through the two PS / 2, or just USB connectors for all three at once. Allows connection optional KVMs of the Family K9XX cascading of up to 3 levels and thus enables control, connecting with KVMs of 16 ports, a total of 4096 PCs. Optionally cables can be ordered octopus type of 1.8m, 3m and 5 m besides special cables 20m two types: single VGA USB or single VGA 2x PS / 2.



Specifications:

Display:	TFT LCD 17" configuration via OSD; Resolution up to 2048 x 1536
Modular Keyboard:	Compatible IBM PC/AT, Windows Keyboard, available in different languages
Touchpad:	Microsoft compatible Touchpad, with wheel mouse emulation
KVM:	8 Port with two 1.8m cables, VGA, USB 2x PS/2
KVM Cascade:	Up to 3 levels to a maximum of 4096 PCs (KVMs optional 16 ports)
Port Selection:	With Keyboard shortcut or OSD; Hot Swap supported
Autoscan:	Adjustable via OSD
Operating system::	Windows 2000/XP/2003 Server, LINUX, Mac OS9/OSx, SunMicro / Vista / Vista64
Power::	External Switching Powersupply 110/240V Output 12V
Dimension::	482mm x 610mm x 44mm; Rack-Size 1U
Enviroment:	0°C – 50°C, 10% - 90% Humidy (non-condensing)
Certification:	FCC Class B, CE, UL, cUL, TUV, CCC
Contenido:	Console with KVM, Rack-Mount Kit, 2x Cables KC-1.8, 1x direct Cable
Warranty:	2 Years
Optional cables:	KC4-1.8 1.8m, KC4-3 3m, KC4-5 5m, KCP-20 20m (VGA & 2xPS/2), KCU-20 20m (VGA & USB)