



## **LCS-KL-2716**

### **Rack-Mount KVM**

### **17" Console with**

### **16 Port KVM**



LCS-KL-2716 is a 17" TFT LCD 4 in 1 LCD KVM with 16 port Combo KVM module. This LCD KVM allows you to connect 16 computers or servers via USB & PS/2 interface. This LCD KVM supports Resolution up to 1280x1024(Analog VGA Input). The touchpad of LCS-KL-2716 are compatible with PS/2 mouse interface. The keyboard is 104 key Keyboard and various language Keyboard are available for option. ( English, Germany, French, Italy , Spanish , U.K, Chinese, Japanese).

#### **FEATURES:**

##### **LCD console drawer**

- ◆ Rack mountable in 19" system rack (1U).
- ◆ Supports PS/2 KB/Mouse.
- ◆ Touchpad mouse owns up-down scrolling function.
- ◆ LED Display for easy status monitoring.
- ◆ One person Easy-Installation.
- ◆ Module design for easy installation and maintenance.
- ◆ The keyboard / touchpad module is also easily removed changing by required with variety of languages.

##### **Modularized KVM switch module**

- ◆ Connects dual interfaces of computers via PS/2 and/or USB
- ◆ Supports Windows 98/98SE/2000/ME/XP/Vista/7/2003 server, Win NT, Unix, Linux, Mac OS9/OSX , SUN Microsystems.
- ◆ Auto PS/2 and USB interface detection
- ◆ Supports resolution up to 1280 x 1024
- ◆ On-Screen-Display (OSD) and Cascade Chain functions.
- ◆ OSD is intuitive menus driven for quick and efficient navigation.
- ◆ An extra combo console for both PS/2 and USB is provided on the rear panel of KVM switch to manage LCD console KVM switch from an external console.
- ◆ Supports cascadable chain with 3 levels, control up to 64/256/4096 PCs, from a single console,cascaded unit does not need special configuration.
- ◆ 3 types of KVM switching:
  - Front panel Push Button
  - Hot-Key on LCD built keyboard or extra combo console PS/2 & USB keyboard
  - Menu driven OSD ( On-Screen-Display )
- ◆ Auto-Scan function ( Time interval can be adjsuted between 5-20 seconds when the Auto-Scan is enabled.)
- ◆ Plug and Play ( Windows 98/SE users might need your Windows CD to install the HID driver for USB keyboard/mouse.)
- ◆ KVM firmware is upgradable via on-board mini-USB download connector and external mini-programmer.


**SPECIFICATIONS:**

Keyboard Languages (Front Modular Keyboard)	104 key Keyboard, compatible to IBM PC/AT, PS/2 keyboard, supports Windows function keys (Germany, English, French, Italian, Spanish, Japanese, Chinese, UK....optional)
TFT LCD Modules	Active Matrix TFT LCD (17") Backlight lifetime: 30,000~50,000 hrs Maximum resolution up to 1280 x 1024 (SXGA) Brightness: 300cd/m <sup>2</sup>
Number Of Computers Controlled	16
Selection Method	1. Front Panel Push Button 2. Hot-Keys on built Keyboard and extra console keyboard 3. OSD (On-Screen-Display)
LED (Front Panel-Push Button)	Red for PC Selection Green for PC On-Line Ready
PC Connectors	16 x HDB-15 female ( PS/2 & USB signal combined )
Extra Console	Video 1 x HDB-15 female Keyboard 1 x 6 pin mini-DIN female / 1 x USB A type female Mouse 1 x 6 pin mini-DIN female / 1 x USB A type female
Firmware Upgrade connector	Mini USB female
Auto-Scan Interval	Adjustable time setting by OSD menu driven
Resolution (Extra console)	Max. Resolution up to 2048 x1536@60Hz DDC, DDC2
Hot Swappable	Yes
Operating System	Windows 98/98SE/ME/2000/XP/Vista/7/2003 server, Linux, Mac OS9/OSX, Sun Microsystems
Power Supply	Universal 90~264VAC input, 12V DC output
Environmental Condition	Operation Temp.: 0~50 degree C Storage Temp.: -20~60 degree C Humidity: 5~95%, non-condensing
Chassis Construction	Metal (meets EIA RS-310C 1U 19" Rack-Mount standard)
Dimensions	L.685.5mm xW.486mm x H.42mm
Weight	N.W. 16.60 KGS G.W. 21.10 KGS
EAN	

